

Maximize to Strong



Glute

MAXNUM MA-A 879 S

**FRAME AND CABLES**

|                        |                                           |
|------------------------|-------------------------------------------|
| Oversized Frame Tubing | Yes                                       |
| Frame Finish           | Proprietary two-coat powder process       |
| Cable Transmission     | Internally Lubricated cables and fittings |
| Tube Thickness         | 3.0 mm.                                   |

**WEIGHT STACK**

|                                         |                                                           |
|-----------------------------------------|-----------------------------------------------------------|
| Total Stack Weight                      | 70 KG / 154 Lbs                                           |
| Weight-Stack Pins                       | Magnetic Pins                                             |
| Points of Adjustment                    | 1 pouts design                                            |
| Guards and pulley Covers                | Stack cover made of acrylic protects                      |
| Self-Lubricating weight stacks Bushings | Solid cold rolled steel plate, with Teflon inner bushings |
| Incremental Weight System               | Yes                                                       |

**USER AMENITIES**

|                                             |     |
|---------------------------------------------|-----|
| Instructional Placards                      | Yes |
| Color-coded Pivots and Points of Adjustment | Yes |
| Personal Storage                            | No  |
| Contoured Seating                           | Yes |

**TECH SPECS**

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Product Dimension ( L x W x H ) | 110 x 131 x 188 / 44" x 52.4" x 75.2" |
| Product Weight                  | 290 kg / 638 lbs                      |
| Certification                   | EN 957 Certified                      |