

Maximize to Strong

FEATURES

Counterbalanced pressing
 Arm lowers start resistance.
 Seat position provides range
 Of motion adjust

MUSCLES USED

Anterior Deltoid , Middle Deltoid
 Triceps Brachii

MOTION DEVELOPED

Shoulder Abduction, Elbow Extension

Shoulder Press

MAXNUM MA-T1006
 S

**FRAME AND CABLES**

Oversized Frame Tubing	Yes
Frame Finish	Proprietary two-coat powder process
Cable Transmission	Internally Lubricated cables and fittings
Tube Thickness	2.5 mm.

WEIGHT STACK

Total Stack Weight	109 KG / 239 Lbs
Weight-Stack Pins	Magnetic Pins
Points of Adjustment	No
Guards and pulley Covers	Stack cover made of acrylic protects
Self-Lubricating weight stacks Bushings	Solid cold rolled steel plate, with Teflon inner bushings
Incremental Weight System	Yes

USER AMENITIES

Instructional Placards	Yes
Color-coded Pivots and Points of Adjustment	Yes
Personal Storage	No
Contoured Seating	Yes

TECH SPECS

Product Dimension (L x W x H)	185 x 122 x 132 / 74" x 48.8" x 52.8"
Product Weight	239 kg / 525 lbs
Certification	EN 957 Certified